



Visuel	Référence	Puissance (W)	CCT	Flux moyen (lm)	Dimensions (mm)
	MOZ-1530S/R	15W	3000°K	1500	D100*H70
	MOZ-1540S/R		4000°K		
	MOZ-1560S/R		6000°K		
	MOZ-2030S/R	20W	3000°K	2000	D120*H80
	MOZ-2040S/R		4000°K		
	MOZ-2060S/R		6000°K		
	MOZ-2530S/R	25W	3000°K	2500	D120*H80
	MOZ-2540S/R		4000°K		
	MOZ-2560S/R		6000°K		
	MOZ-1530E	15W	3000°K	1500	D100*H30
	MOZ-1540E		4000°K		
	MOZ-1560E		6000°K		
	MOZ-2030E	20W	3000°K	2000	D120*H37
	MOZ-2040E		4000°K		
	MOZ-2060E		6000°K		
	MOZ-2530E	25W	3000°K	2500	D120*H37
	MOZ-2540E		4000°K		
	MOZ-2560E		6000°K		
	MOZFAT-1230S/R	12W	3000°K	1200	D100*H185
	MOZFAT-1240S/R		4000°K		
	MOZFAT-1260S/R		6000°K		



codes/références : S pour saillie - R pour rail - E pour encastré.